









NQ512BR NQ512BG NQ512BB NQ512BW

# DIGITAL MEDIA RECEIVER

🗥 nakamichicaraudio.com

f nakamichi.global

🙆 nakamichi.caraudio

## CONTENTS

Warnings&Precautions		
ISED Statement	26	ΞN
Product Features	2 6	ΞN
Installation	3 8	ΞN
Installation Procedures	3 8	ΞN
Installation Opening		
To Install The Car Radio	3 8	ΞN
Accessory List		
Dimension(Unit:mm)		
Wiring Diagram		
Basic Functions Of Panel Keys	5 F	ΕN
Remote Operation		
Basic Operation		
Radio Operation		
Start Listening		
USB Playback		
AUX Input		
Bluetooth Operation		
Bluetooth Pairing	2 1	EN
Bluetooth Basic Operation	2 1	EN
Bluetooth Music Operation		
APP Operation	ינ	
APP Download	יו נ	
APP Connection		
APP Operation		
External Microphone		
Audio Settings		
Audio Settings List		
Preset EQ Select		
User EQ Setup		
Loundness Setup		
Bass Adjustment		
Treble Adjustment		
Balance Adjustment		
Fader Adjustment		
Audio Setup Reset		
Tuner Settings	3 8	ΞN
Tunner Settings List	3 8	ΞN
Stereo/Mono Select		
DX/Local Select		
RDS ON/OFF	3 E	ΞN
Tuner Area Select		
Clock Settings		
Clock Settings List	1 [	ΞN
Clock Format Settings	1 8	ΞN
Clock Adjust	4 E	ΕN
Display Settings	4 8	ΕN
Display Settings List	1 E	ΞN
Spectrum On/Off14	4 8	ΕN
ID3 On/Off	1 E	ΞN
System Version		
Trouble Shooting		
Speaker Connection	5 E	ΕN
Specification	۶E	ΞN

## WARNINGS & PRECAUTIONS

To avoid risk of serious injury or possble violation of laws, please read the following thoroughly before installation or connecting.

- This product is designed specifically for use with 12 volt, negative ground electrical systems only.
- Having the wiring and installation done by expert. Be sure to diconnect the cable from the negative battery terminal while installtion.
- This apparatus shall not be exposed to dripping or splashing, and no object filled with liquids, shall be placed on the apparatus.
- Fuses shall be replaced only with the correct type and fuse value, and only when the apparatus is powered off.
- To prevent a short circuit.never put or leave any metallic objects(such as coins or metallic tools)inside the unit.
- Never set the volume of this product so high that you cannot hear outside traffic and emerency vehicles.

## FCC STATEMENT

This equipment has been tested and found to comply with the limits for a Class B digital device, pursuant to part 15 of the FCC Rules. These limits are designed to provide reasonable protection against harmful interference in a residential installation. This equipment generates, uses and can radiate radio frequency energy and, if not installed and used in accordance with the instructions, may cause harmful interference to radio communications. However, there is no guarantee that interference will not occur in a particular installation. If this equipment does cause harmful interference to radio or television reception, which can be determined by turning the equipment off and on, the user is encouraged to try to correct the interference by one or more of the following measures:

- Reorient or relocate the receiving antenna.
- Increase the separation between the equipment and receiver.
- Connect the equipment into an outlet on a circuit different from that to which the receiver is connected.
- Consult the dealer or an experienced radio/TV technician for help.

**Caution:** Any changes or modifications to this device not explicitly approved by manufacturer could void your authority to operate this equipment.

This device complies with part 15 of the FCC Rules. Operation is subject to the following two conditions:

1. This device may not cause harmful interference.

2. this device must accept any interference received, including interference that may cause undesired operation.

### **RF Exposure Information**

This equipment complies with FCC radiation exposure limits set forth for an uncontrolled environment. This equipment should be installed and operated with minimum distance 20cm between the radiator and your body.

## **ISED STATEMENT**

**English:** This device contains licence-exempt transmitter(s)/receiver(s) that comply with Innovation, Science and Economic Development Canada's licence-exempt RSS(s). Operation is subject to the following two conditions:

1. This device may not cause interference.

2. Cause undesired operation of the device.

The digital apparatus complies with Canadian CAN ICES-3 (B)/NMB-3(B).

French: Cet appareil contient des émetteurs/récepteurs exempts de licence qui sont conformes aux RSS exemptés de licence d'Innovation, Sciences et Développement économique Canada.L'exploitation est soumise aux deux conditions suivantes :

1. Cet appareil ne doit pas provoquer d'interférences.

2. Cet appareil doit accepter toute interférence, y compris les interférences susceptibles de provoquer un fonctionnement indésirable de l'appareil.

l'appareil numérique du ciem conforme canadien peut -3 (b) / nmb -3 (b).

This device meets the exemption from the routine evaluation limits in section 2.5 of RSS 102 and compliance with RSS 102 RF exposure, users can obtain Canadian information on RF exposure and compliance.

Cet appareil est conforme à l'exemption des limites d'évaluation courante dans la section 2.5 du cnr - 102 et conformité avec rss 102 de l'exposition aux rf, les utilisateurs peuvent obtenir des données canadiennes sur l'exposition aux champs rf et la conformité.

This equipment complies with Canada radiation exposure limits set forth for an uncontrolled environment.

Cet équipement est conforme aux limites d'exposition aux rayonnements du Canada établies pour un environnement non contrôlé.

This equipment should be installed and operated with minimum distance 20cm between the radiator & your body.

Cet équipement doit être installé et utilisé à une distance minimale de 20 cm entre le radiateur et votre corps.

### **PRODUCT FEATURES**

LCD: VA-LCD DISPLAY

Bluetooth: Version 5.1

Bluetooth Music: Support

Push to Talk: Support

EQ: 32 band, 8 Preset

Pre-Output: 4CH x 2V

Max Power: 4 x 50W Radio: Preset 18FM,12AM, RDS APP Control: iOS and Android Phone Charge: Front USB 1A Audio Format: MP3, WMA, AAC, FLAC

## INSTALLATION

### Installation Procedures

First complete the electrical connections and then check for correctness.

### Installation Opening

This unit can be installed in any dashboard Having an opening as shown below:



### To Install The Car Radio

Be sure you test all connections first, and then follow these steps to install this unit.

1. Make sure the ignition is turned off, and then disconnect the cable from thevehicle battery's negative (-) terminal.

2. Disconnect the wire harness and the antenna.

3. Remove the detachable panel and decorative enclosure frame and place on one side.

4.Insert the two brackets into the left and right sides of the chassis, as shown in the following figure, and separate the chassis from the sleeve.



5.Insert the installation sleeve into the center console to be installed, and bend the clip using a screwdriver. Make sure the locking rod is flush with the mounting sleeve and does not protrude.

6.Connect cables as shown in the Wiring diagram.

7.Insert the car radio into the mounting sleeve.

8.Install decorative enclosure frame.

## ACCESSORY LIST

Please check the following accessories after opening the package:





## DIMENSION(UNIT:MM)











### WIRING DIAGRAM



POWER/SPEAKER CONNECTOR		
Color	Name	
Red	Ignition Wire	
Black	GND	
Blue	Amplifier Control	
Yellow	Battery(+)	
Green/Black	Rear Left Speaker -	
Green	Rear Left Speaker +	
White/Black	Front Left Speaker -	
White	Front Left Speaker +	
Gray/Black	Front Right Speaker -	
Gray	Front Right Speaker +	
Purple/Black	Rear Right Speaker -	
Purple	Rear Right Speaker +	

### **BASIC FUNCTIONS OF PANEL KEYS**

То	Radio Status	USB/BT Music Status	
	Seek a station manually	Previous/Next track	
1	Preset 1	Playback/Pause	
2	Preset 2	Intro Playback	
з	Preset 3	Repeat Playback	
4	Preset 4	Random Playback	
5 E	Preset 5/Preset 6	Previous/Next folder	
⇒ I BAND	Return key function in menu state In radio mode, press to toggle FM1/FM2/FM3/AM1/AM2		
்பாபா	Press to mute, Press an hold to shutdown In call mode, press to end call		
I AUTO	Short press to voice key (bluetooth connection required) In radio mode, press to radio to auto search the channel		
っ I MODE	When the call comes, short press to answer the call (bluetooth connection required)   In call mode, short press to switch sound channel (car horn or handset)   Short press to switch mode function		



## **REMOTE OPERATION**



### **Basic Operation**

То	Operation (panel)
Power on	Press പ്രസ്സ്സ് പ്രസ്സ്സ് പ്രസ്സ്സ്സ് പ്രസ്സ്സ്സ് പ്രസ്സ്സ്സ് പ്രസ്സ്സ്സ് പ്രസ്സ്സ് പ്രസ്സ്സ് പ്രസ്സ് പ്രസ്സ് പ
Power off	Press and hold പ്രസ്സന്ത
Mute	Press ധI <b>MUTE</b>
Volume up and down	Turn the knob
Source select	Press <b>&gt; I mode</b>
Menu	Press the knob
Return	Press 🗅 I BAND (In menu status)
Turn on voice	Press  I AUTO (Bluetooth is connected)

## **RADIO OPERATION**

### Start Listening

То	Operation (panel)	Remark
Auto memory	Press and hold 🎚 I AUTO	18 FM/12AM
Band selection	Press <b>⊐IBAND</b>	FM1/FM2/FM3/AM1/AM2
Seek a station manually	Press 阔 🍽	
Search the next or previous frequency step by step	Press and hold Id  I	
Store a station	Press and hold 1-6	

### **USB PLAYBACK**

То	Operation (panel)
Track selection Fast playback	Press IAA >>I Press and hold IAA >>I
Playback/Pause	Press 1
Track pre-play	Press 2
Repeat playback	Press 3 • REPEAT ONE.REPEAT DIR.REPEAT ALL
Random playback	Press 4 • ON/OFF
Folder selection	Press <b>5 6</b>

### **AUX INPUT**

1.Connect a portable audio player(commercially available). Auxiliary input jack







Portable audio player

Auxiliary input jack

3.5mm stereo mini plug with "L"shaped connector. (commercially available).

2.Press[ > I MODE ] buttons to select AUX IN.

3.Turn on the portable audio player and start playback.

### **BLUETOOTH OPERATION**

### **Bluetooth Pairing**

The first time pair mobile phone with receiver, please follow below steps:

- 1.When there is no pairing, in any mode, the BT1 on the LCD will flash, and the pairing can be performed at this time.
- 2.Turn on the phone's Bluetooth to Search NQ512B.
- 3.Click on the NQ512B on the phone to connect. After the connection is successful, the BT1 will stop flashing.
- 4.When pairing is complete, the mobile phone audio will automatically transfer to the car audio system whenever a call is made or received, or when the mobile phone plays music.

#### Note:

For more details of bluetooth pairing, please refer to the owner's manual for your mobile phone.

#### **Bluetooth Basic Operation**

То	Operation (panel)
Answer a call	Press <b>NI MODE</b>
Switch the car horn or mobile phone handset	Press 🔉 I MODE (In a call)
End a call	Press പ്രത്വന്ന a call)
Adjust call volume	Turn on the knob

#### **Bluetooth Music Operation**

То	Operation (panel)	
Previous track	Press I	
Next track	Press <b>&gt;&gt;</b>	
Playback/Pause	Press 1	

## APP OPERATION

### APP Download

Please go to the APPALE APP Store or Google Play Store and search [Nakamichi AMC] app,after downloading the APP,install it on your Appale&Android devices.

### **APP** Connection

- 1. Open the [Nakamichi AMC] APP, click [] to search for NQ512B.
- 2. Click NQ512B to connect, the [] will be red after the connect is successful.



### APP OPERATION



### **EXTERNAL MICROPHONE**



### Note:

Since the panel microphone is far from the driver's position, when using an external microphone, you can get better voice calls.

## AUDIO SETTINGS

1.Press the knob to enter the [MENU].

2.Turn the knob to select [AUDIO], then press the knob.

### Audio Settings List

Menu	Adjustment
PRESET EQ	USER/NATURAL/POP/CLASS/ROCK/JAZZ/FLAT/SUPER BASS
	□ 30Hz/60Hz/80Hz/100Hz/120Hz/160Hz/250Hz/400Hz 600Hz/ 800Hz/1KHz/1.5KHz/2KHz/2.5KHz/3KHz/3.5K/4K/5K/6K/7K/8K/ 9K/10K/11K /12K/13K/14K/15K/16K/17K/18K/19K
LOUD	OFF/ON
BASS	BASS -7 ~ +7
TREBLE	TREBLE -7 ~ +7
BAL	BALAN L7-L0,0,R1-R7
FADER	FADER R7-R0,0,F1-F7
AUDIO RESET	NO/YES

#### Preset EQ Select

1.Turn the knob to select [PRESET EQ ], then press the knob. 2.Turn the knob to select [USER/NATURAL/POP/CLASS/ROCK/ JAZZ/FLAT/SUPER BASS].

### User EQ Setup

1.Turn the knob to select [PRESET EQ ], then press the knob. 2.Turn the knob to select [USER], then press the knob. 3.Turn the knob to select frequency for adjustment.

#### Loundness Setup

1.Turn the knob to select [LOUND],then press the knob. 2.Turn the knob to select [OFF/ON].

#### **Bass Adjustment**

1.Turn the knob to select [BASS], then press the knob. 2.Turn the knob to adjustment [-7 to +7].

#### Treble Adjustment

1.Turn the knob to select [TREBLE], then press the knob. 2.Turn the knob to select [-7 to +7].

### **Balance Adjustment**

1.Turn the knob to select [BAL], then press the knob. 2.Turn the knob to select [ L7-L0 toR1-R7].

### Fader Adjustment

1.Turn the knob to select [FADER], then press the knob. 2.Turn the knob to select [ R7-R0 toF1-F7].

### Audio Setup Reset

1. Turn the knob to select [AUDIO RESET], then press the knob. 2. Turn the knob to select [NO/YES].

## TUNER SETTINGS

...

1.Press the knob to enter the [MENU]. 2.Turn the knob to select [TUNER],then press the knob.

....

Tunner	unner Settings List			
Menu	Adjustmen	ıt		
TUNER	STEREO/MONO		NONE/NEWS/AFFAIRS/INFO/SPORT/	
	DX/LOCAL		EDUCATE/DRAMA/CULTURE/SCIENCE/	
	RDS OFF/C	N	VARIED/POP M/ROCK M/EASY M/	
		TA OFF/ON	LIGHT M/CLASSICS/OTHER M/WEATHER/	
		AF ON/OFF	FINANCE/CHILDREN/SOCIAL/RELIGION/	
		AI ON/ON	PHONE IN/TRAVEL/LEISURE/JAZZ/	
		EON OFF/ON	COUNTRY/NATION M/OLDIES/FOLK M/	
		REG OFF/ON	DOCUMENT	
		PTY OFF/ON		
	AREA EUR/USA/ASIA/RUSS			

### Stereo/Mono Select

Turn the knob to select [STEREO or MONO], then turn the knob select [STEREO/MONO].

### **DX/Local Select**

Turn the knob to select [LOC or DX], then turn the knob select [DX /LOCAL]. Remark: DX:Distant exchange

### **RDS ON/OFF**

Turn the knob to select [RDS OFF], then turn the knob select [RDS OFF, ON].

### **Tuner Area Select**

Turn the knob to select [AREA], then turn the knob select [EUR/USA/ASIA/RUSS].

## CLOCK SETTINGS

1.Press the knob to enter the [MENU].

2.Turn the knob to select [CLOCK], then press the knob.

### **Clock Settings List**

Menu	Adjustment
CLK FRMT	12H/24H
CLK ADJ	00:00

### **Clock Format Settings**

1.Turn the knob to select [CLK FRMT], then press the knob. 2.Turn the knob to select [12H/24H].

#### Clock Adjust

1.Turn the knob to select [CLK ADJ], then press the knob.

2.Turn the knob to adjustment.

3.Press the knob to switch the clock/minute adjustment.

### **DISPLAY SETTINGS**

### **Display Settings List**

Menu	Adjustment
SPECTRUM	OFF/ON
ID3 TAG	OFF/ON
VERSION	VER 3.1

#### Spectrum ON/OFF

1.Turn the knob to select [SPECTRUM],then press the knob. 2.Turn the knob to select [OFF/ON].

#### ID3 ON/OFF

1.Turn the knob to select [ID3 TAG], then press the knob. 2.Turn the knob to select [OFF/ON].

#### System Version

Turn the knob to select [VERSION], then press the button to query the system version information.

## **TROUBLE SHOOTING**

<b>Not work</b> Fuse blown	<b>Remedy</b> Replace the fuse: sma <b>l</b> 10A(Red)
<b>Not responding</b> System problem	Reset the unit
<b>Can't turn on voice</b> Bluetooth is not connected Phone does not support voice	Connect Bluetooth N.A
<b>Not playing</b> Incorrect device format Device error Unsupported audio file	Reformat Replacement device Replace supported audio files
<b>Radio reception is poor</b> Poor contact of radio antenna Poor signal at location	Reconnect the radio antenna Change to other positions
Remote control is invalid Remote control battery is low	Replace CR2025 battery

**Bluetooth call is poor** Microphone is too far away

Speak into the microphone

## **SPEAKER CONNECTION**

Do not connect the speaker leads of the power cord to the car battery; otherwise, the unit wil be seriously damaged.

Before oconnecting the speak leads of the power cord to the speakers, check the speaker wiring in your car.







## SPECIFICATION

Power supply Requirement	DC 12V
Maximum power output	50W X 4CH
Speaker impedance	4 - 8 Ohm
Unit Dimensions(WxHxD)	178 x 111 x 50 mm
Weight	0.44 kg
Fuse	10 A
	Maximum power output Speaker impedance Unit Dimensions(WxHxD) Weight

RADIO	FM Frequency Range	87.5MHz-108.0MHz
	AM Frequency Range	522 KHz~1620 KHz
	Preset	18FM,12AM

USB INDEX	Usable Audio Formats:	MP3, WMA, AAC, FLAC
	USB Port Type:	2.0
	USB Maximum Capacity:	64GB
	USB Charging:	5V/1A
	Frequency Response:	20 Hz - 20 KHz
	S/N Ratio:	60 dB

ETOOTH	Version	Bluetooth 5.1
	BT Profile supports:	A2DP, AVRCP, HFP
BLUET	Range of frequency:	2.4 GHz spectrum



CONNECT WITH US ONLINE TO EXPLORE NAKAMICHI'S COMPLETE RANGE, INSTRUCTIONS & SOFTWARE DOWNLOADS AND WARRANTY REGISTRATION.

WWW.NAKAMICHICARAUDIO.COM

f nakamichi.global 🙆 nakamichi.caraudio Nakamichi Corp, Japan Made in China | 中國製造