

Nakamichi!

Nakamichi

NSE
SERIES



NSE5718

5x7" 2-WAY COAXIAL SPEAKER
ENCEINTE COAXIALE 2 VOIES 5x7" / ALTAVOZ COAXIAL DE 2 VÍAS DE 5x7"
5x7" 2-ПОЛОСНЫЙ КОАКСИАЛЬНЫЙ ДИНАМИК / 5x7" 兩路同軸揚聲器

PEAK POWER
200W
N-POWER 30W

Nakamichi

Nakamichi

Nakamichi

NSE5718

5x7" 2-WAY COAXIAL SPEAKER
ENCEINTE COAXIALE 2 VOIES 5x7" / ALTAVOZ COAXIAL DE 2 VÍAS DE 5x7"
5x7" 2-ПОЛОСНЫЙ КОАКСИАЛЬНЫЙ ДИНАМИК / 5x7" 兩路同軸揚聲器

COMPLETE YOUR VEHICLE'S SETUP WITH NAKAMICHI'S COMPATIBLE PRODUCTS

CONNECT WITH US ONLINE TO EXPLORE NAKAMICHI'S COMPLETE RANGE, INSTRUCTIONS & SOFTWARE DOWNLOADS AND WARRANTY REGISTRATION.

WWW.NAKAMICHICARAUDIO.COM

[nakamichi.global](#) [nakamichi.caraudio](#)

Nakamichi Corp. Japan Made in China | 中國製造



Frequency Response:	70-3.8kHz
Peak Power:	200 Watts
N-power:	30 Watts
Speaker Type:	5x7" (12.6x18.3cm) 2-way
Mounting Depth:	>2" (50mm)
Sensitivity (1pt):	84±3dB
Net Mass (1pt):	Approx. 1.3kg
Impedance:	4Ω

What's in The Box

1. Speakers x 2pcs
2. (Grille Net + Frame) x 2pcs
3. Screw Ø4x20mm x 8pcs
4. Gaskets x 8pcs

Composite Polypropylene Cone

Our treated composite polypropylene cone is extremely rigid but still lightweight, allowing it to reproduce even deeper and more powerful bass notes.

PEI Dome Tweeter

PEI, or also known as Polyetherimide, is lightweight, heat resistant and retains its shape even after prolonged use, allowing accurate sound reproduction in all situations.

Foam Surround

Our foam surround is treated to maintain a constant level of sound reproduction during long periods of operation within your vehicle.

Installation

1. Turn on the car ignition key.
2. If the power is on, the click noise generated by the connection may damage the speaker. The connection may damage the speaker.
3. Fold the mounting template from the packing box.
4. Make the cut-out hole and the 4 bolt holes. (Fig.1)
5. Cut out the marked area and drill the bolt holes. (Fig.2)
6. Remove the grille net. (Fig.3)
7. Strip the speaker wires and connect them to the amplifier. Consult the diagram below. Be sure to connect corresponding terminals. i.e. "+" to "+" and "-" to "-".
8. Connect the speaker cable to the speaker terminal while holding the lower portion of the speaker terminal.
9. Do not interfere with any inner parts, such as the door handles, arm rests etc.
10. Mount on the speaker as shown below.
11. Press and insert the edges of the grille net. If you like, the speaker grille can be mounted without the grille net.

5x7" 2-WAY COAXIAL SPEAKER
ENCEINTE COAXIALE 2 VOIES 5x7" / ALTAVOZ COAXIAL DE 2 VÍAS DE 5x7"
5x7" 2-ПОЛОСНЫЙ КОАКСИАЛЬНЫЙ ДИНАМИК / 5x7" 兩路同軸揚聲器

Nakamichi

注：红色线为安装模板，要求轧虚线孔。
尺寸：外圈232x162mm，内圈185x128mm，孔位如图，4-Ø3mm。

日期	更改内容	签名
2022. 5. 12	1. 产品类别描述增加法语 2. 二维码处增加推荐产品和Nakamichi Corp. Japan	靖