

彩盒尺寸:360*209*98mm

材质:350G灰底白+Am(E), 四色印刷, 过哑膜, 配一张圆形透明贴纸封口

Nakamichi

Nakamichi

NSI SERIES



NSI165

6.5" 2-WAY COAXIAL SPEAKER

ALTAVOZ COAXIAL DE 2 VIAS DE 6.5" / 6.5"二路同轴扬声器

ENCEINTE COAXIAL 2 VOIES 6.5" / 6.5" 2-ПОЛОСНЫЙ КОАКСИАЛЬНЫЙ ДИНАМИК

PEAK POWER
200W
N-POWER 30W

Nakamichi

Nakamichi

Nakamichi

NSI165

6.5" 2-WAY COAXIAL SPEAKER

ALTAVOZ COAXIAL DE 2 VIAS DE 6.5" / 6.5"二路同轴扬声器

ENCEINTE COAXIAL 2 VOIES 6.5" / 6.5" 2-ПОЛОСНЫЙ КОАКСИАЛЬНЫЙ ДИНАМИК



COMPLETE YOUR VEHICLE'S SETUP WITH NAKAMICHI'S COMPATIBLE PRODUCTS



CONNECT WITH US ONLINE TO EXPLORE NAKAMICHI'S COMPLETE RANGE, INSTRUCTIONS & SOFTWARE DOWNLOADS AND WARRANTY REGISTRATION.

WWW.NAKAMICHICARAUDIO.COM

nakamichi.global | nakamichi.caraudio

Nakamichi Corp. Japan | Made in China | 中國製造



Speaker Type: 6.5" (168mm) 2-way	Mounting Depth: >52" (64mm)	Peak Power: 200 watts	Sensitivity (dB/W/m): 89 ± 3dB	Impedance: 4Ω	Voice Coil: ASV Ø25.5mm	Magnet Mass: 10.6 Oz (301g)	Net Mass (Pr): Approx. 1.4kg	1. Speakers x 2PCS	2. Screw (Øx25mm) x 8PCS	3. 20cm Speaker cable x 2PCS
----------------------------------	-----------------------------	-----------------------	--------------------------------	---------------	-------------------------	-----------------------------	------------------------------	--------------------	--------------------------	------------------------------

Specifications

Speaker Type: 6.5" (168mm) 2-way
Mounting Depth: >52" (64mm)
Peak Power: 200 watts
Sensitivity (dB/W/m): 89 ± 3dB
Impedance: 4Ω
Voice Coil: ASV Ø25.5mm
Magnet Mass: 10.6 Oz (301g)
Net Mass (Pr): Approx. 1.4kg

What's in the Box

1. Speakers x 2PCS
2. Screw (Øx25mm) x 8PCS
3. 20cm Speaker cable x 2PCS

Installation Option: Mount On Door

You can mount the speakers on the front/rear door of your car.

- Make sure that nothing obstructs around the mounting location of the door.
- A hole for mounting may already be cut out of the inner panel of the door (front or rear). If so, you need to modify the speaker terminals, frame or magnet (such as the window), etc. Also ensure that the speaker does not touch any inner fittings, such as the window cranks, door handles, trim rests etc.
- Turn off the car ignition key.
- If the power is on, the click noise generated by the connection may damage the speakers.
- Ensure that the speaker terminals, frame or magnet do not interfere with any inner parts.
- Connect the speaker wires and connect them to the amplifier.
- Consult the diagram below. Be sure to connect corresponding terminals, i.e. "+" to "+" and "-" to "-". Connection with reversed polarity will degrade the quality of production.
- Connect the provided speaker cord to the speaker terminal while holding the lower portion of the speaker terminal.

Composite Glass Fibre Cone

Our glass fibre cone is built to be high-strength but still lightweight, allowing the speaker to reproduce all sounds gracefully, from low bass to delicate highs.

High Temperature Aluminium Voice Coil

Specialty designed voice coil ensures reliable performance even under high temperatures and loads.

Durable Rubber Surround

Rubber surround for flexibility and durability in extreme conditions within your vehicle.

Experience enhanced acoustic performance with the Nakamichi NSI165 2-way coaxial speaker. Our enhanced cone surface treatment is designed to deliver enhanced acoustic performance whilst the premium rubber surround helps with speaker excursion to deliver premium sound.

Dimensions (unit: mm)

注:红色线为安装模板, 要求直接轧虚线孔, 不印刷 尺寸:外圈Ø168mm, 内圈Ø141mm, 孔位Ø158mm, 4-Ø3mm.

日期	更改内容	签名
2022.5.30	二维码增加描述Nakamichi Corp. Japan	晴

NSI165

Nakamichi