

70x100mm, 正反面 105克铜版纸

 Nakamichi

NC-6L
Color CMD Camera



SPECIFICATIONS

NC-6L

Image Sensor:	H7360S
Optical Format:	1/6.25-inch
Optical FOV:	D 120° H 85° V 60°
Optical Distortion:	< -48%
Array Size:	CVBS(NTSC)
Pixel Size:	3.6um(H)x3.6um(V)
Construction:	1xGlass, 2xPlastic
Operating Temperature:	-20 C ~+65 C
Power Supply:	12V

www.nakamichicaraudio.com

正面

INSTALLATION

Please read these instructions carefully before installation and use. Installation should be performed by professional staff.

1. Wire Connection

Connect the 12V power to the red jack using the Included 1m cable. Use the included 5m cable to connect the yellow RCA to your video monitor.

Attention: The camera switch is controlled by the reverse Gear shift.

2. Installation Method

The camera can be installation the following way:

- External installation (Fig.1)
- Bracket-mount: Install in the rear bumper or on the License plate. Fix the camera with screws.




Fig.1

WHAT'S IN THE BOX

CMD Camera (x1pc) Instruction Manual (x1pc)
1m Power Cable (x1pc) 5m Video Cable (x1pc)
Screws/Nuts (for bracket mount) (x2pcs)

背面