

NC-A100

User Manual





CONNECT WITH US ONLINE TO EXPLORE NAKAMICHI'S COMPLETE RANGE, NOTE AT STATE OF THE STATE OF T

WWW.NAKAMICHICARAUDIO.COM

f nakamichi.global anakamichi.caraudio

Nakamichi Corp, Japan Made in China | 中國製造

CAR CAMERA

@ nakamichi.caraudio

SPECIFICATIONS

Image Sensor Color CMD(Photosensitive Chip)

Lens Angle 120° TV System PAL

Effective Pixels 1280(H)×720 (V)

Horizontal Resolution 720P

Sensing Area 4.4mm X3.1mm Shutter Speed 1/60-20 us

Video Output Normal video out: 1.0Vp-p,75Ω

Power Supply

Operating Temperature -30°C~+70°C RH 95% Max Storage Temperature -30°C~+70°C RH 95% Max

IP68 Waterproof

INSTALLATION

Please read these instructions carefully before installation and use. Installation should be performed by professional staff.

A. INSTALLATION INSTRUCTION FOR EMBEDDED/PUNCHING CAMERA









- 1.Before making a hole in the car, please make sure the diameterof the camera equal to the drill bit.
- 2. According to the arrow indicated direction (up) to install.
- 3. Insert the lead wire of the camera into the hole and then begin to install the camera.
- 4.As above diagram, using two thumbs to push the camera into the car with balanced forces.

B. INSTALLATION INSTRUCTION FOR HANGING CAMERA











- 1. For easy installation, please use drill to open a screw hole at the appropriate position in the rear license plate of the car.
- 2. Tighten the first screw into the screw hole with screw driver.
- 3. Please adjust the camera's position according to the actual display on the monitor.
- 4. After adjustment, please use drill to open the second screw hole.
- 5. After fixing the second screw, all the installation are finished.

C. LNSTALLATION INSTRUCTION FOR LICENSE PLATE









- 1. Take out of the license plate, adjust the direction up and down.
- 2. Alignment license plate to the installation location of the car.
- 3. Tighten the screws,install the license plate frame camera.
- 4. Adjust up and down angles of the camera, then fixed the screw.


D. ASSEMBLY DIAGRAM FOR EXCHANGING THE FRONT HOUSING OF PUNCHING/EMBEDDED AND HANGING CAMERA.





- As above diagram shown, change the front housing of embedded / punching camera to hanging one.
- 2. As above diagram shown, change the front housing of hanging camera to embedded/punching one.

IMAGE INSTRUCTION



WHAT'S IN THE BOX

- 1. Camera x1pc
- 2.6m Video Cablex1pc
- 3. Ø7×10 mm Screw x3pcs

- 4. User Manual x1pc
- 5. 3M Adhesive x1pc