



C:0
M:91
Y:87
K:0

彩盒尺寸：360x285x120mm 双插盒型 350g裱坑 四色印刷 过哑膜

Specifications

Speaker Type: 6x9" 4-way
Mounting Depth: >3.3" (84mm)
N-Power: 70W (1pc), 140W (2pc)
Peak Power: 490W (1pc), 980W (2pc)
Sensitivity (dB/W/m): 87-93dB
Frequency response: 57 ~ 22000Hz
Impedance: 4Ω
Voice Coil: ASV Ø25mm
Magnet Weight: 20 OZ
Net Mass (1pc): Approx. 2.8kg
1. Speakers x 2pcs
2. Frame x 2pcs
3. Screw Ø4x30mm x 8pcs
4. Gaskets x 8pcs

What's In The Box

1. Speakers x 2pcs
2. Frame x 2pcs
3. Screw Ø4x30mm x 8pcs
4. Gaskets x 8pcs

Composite Injection

Our treated composite injection cone is extremely rigid but still lightweight, allowing it to reproduce even deeper and more powerful bass notes.

Silk Dome Tweeter

Silk is light weight material, heat resistant and retains its shape even after prolonged use, allowing accurate sound reproduction in all situations.

Rubber Surround

Our rubber surround is treated to maintain a constant level of sound reproduction during long periods of operation within your vehicle.

Dimensions (unit: mm)

1. Turn off the car ignition key.
2. Cut out the mounting template from the packaging box.
3. Paste the template on the location selected for mounting the speaker.
4. Mark the cut-off hole and the 4 bolt holes. (Fig.1)
5. Cut out the marked area and drill the bolt holes. (Fig.2)
6. Remove the gasket. (Fig.3)
7. Mount the speaker on the location selected for mounting the speaker.
8. Mount on the speaker as shown below.
9. Press and reset the edges of the gasket.
10. The speaker gasket can be mounted without the gasket, if you like.

Option: Mount on the Rear Tray

You can mount the speakers on the rear tray of your car. Make sure that nothing obstructs around the mounting location of the rear tray. If so, you need to modify the board only. A hole for mounting can be made on the board only. Also ensure that the speaker gasket does not touch any metal part, such as the window frame, door handles, arm rests etc.

Installation

1. Turn off the car ignition key.
2. Cut out the mounting template from the packaging box.
3. Paste the template on the location selected for mounting the speaker.
4. Mark the cut-off hole and the 4 bolt holes. (Fig.1)
5. Cut out the marked area and drill the bolt holes. (Fig.2)
6. Remove the gasket. (Fig.3)
7. Mount the speaker on the location selected for mounting the speaker.
8. Mount on the speaker as shown below.
9. Press and reset the edges of the gasket.
10. The speaker gasket can be mounted without the gasket, if you like.

Option: Mount on the Rear Tray

You can mount the speakers on the rear tray of your car. Make sure that nothing obstructs around the mounting location of the rear tray. If so, you need to modify the board only. A hole for mounting can be made on the board only. Also ensure that the speaker gasket does not touch any metal part, such as the window frame, door handles, arm rests etc.

6x9" 4-Way Coaxial Speaker
Altavoces concéntricos de 6x9 pulgadas y 4 vías/6x9"四路同軸揚聲器
6x9" 4-way Koaxiallautsprecher

Nakamichi



NSG6959

6x9" 4-way Coaxial Speaker

Altavoces concéntricos de 6x9 pulgadas y 4 vías/6x9"四路同軸揚聲器
6x9" 4-way Koaxiallautsprecher

PEAK POWER
980W
N-POWER 140W



NSG SERIES



COMPLETE YOUR
VEHICLE'S SETUP
WITH NAKAMICHI'S
COMPATIBLE PRODUCTS



CONNECT WITH US ONLINE TO EXPLORE NAKAMICHI'S COMPLETE RANGE,
REQUESTING LITERATURE, DOWNLOADS AND WARRANTY REGISTRATION.
WWW.NAKAMICHICARAUDIO.COM
Facebook: nakamichi.global Instagram: nakamichi.caraudio
Nakamichi Corp. Japan Made in China | 中國製造

RoHS CE

